

ASME B29.10M-1997
(Revision of ASME B29.10M-1994)

HEAVY DUTY OFFSET SIDEBAR POWER TRANSMISSION ROLLER CHAINS AND SPROCKET TEETH

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**



HEAVY DUTY OFFSET SIDEBAR POWER TRANSMISSION ROLLER CHAINS AND SPROCKET TEETH

ASME B29.10M-1997

(Revision of ASME B29.10M-1994)

Date of Issuance: October 20, 1997

This Standard will be revised when the Society approves the issuance of a new edition. There will be no addenda or written interpretations of the requirements of this Standard issued to this edition.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Consensus Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment which provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not "approve," "rate," or "endorse" any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable Letters Patent, nor assume any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of the infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations issued in accordance with governing ASME procedures and policies which preclude the issuance of interpretations by individual volunteers.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
345 East 47th Street, New York, NY 10017

Copyright © 1997 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All Rights Reserved
Printed in U.S.A.

FOREWORD

(This Foreword is not part of ASME B29.10M-1997.)

Chains of the type covered by this Standard were introduced in the United States late in the 19th Century. As their popularity increased, the number of chains and manufacturers grew. As one manufacturer developed a successful size chain, or family of chains, others soon duplicated it and a large number of chains came into being.

In spite of efforts at standardization, the Corps of Engineers, United States Army, found during the Korean incident of 1950-53 that lack of adequate standardization of power transmission chains still resulted in the incapacitation of many cranes and shovels. For this reason, the Corps of Engineers requested the Society of Automotive Engineers to expand the scope of ASA Sectional Committee B29 to cover this group of chains. On May 13, 1956, the Corps of Engineers request was approved by the ASA B29 Committee and the ASA B29.10 Subcommittee was formed. Upon approval by the American Standards Association in April 1962, the first standard for ASA B29.10 chains and sprockets was published. The Standard described the physical dimensions of the chain components and sprockets, and defined the minimum static properties for the chains.

In 1970, this Standard was revised to include Drive Selection information in a Supplementary Section and to convert fractions to decimal-inch, and include metric dimensions in SI Units.

In September 1962, the Engineering Steel Chain Division of the ACA began a research program to develop ratings for the ANSI B29.10 chains. Capacity information on the smaller B29.1 chains already developed in research programs sponsored by the Roller Chain Division of the ACA was made available to the Engineering Steel Chain Division. Member companies contributed information from their own research programs. Special dynamic test equipment was built to enable obtaining wear and capacity data on very large chains. The horsepower capacities published as supplementary information in this Standard resulted from this combined research effort; they are considerably higher than previously accepted by the industry. At all speeds and for all sprocket sizes, the capabilities of ANSI B29.10 chain drives exceeded those previously accepted by the industry.

This Standard was approved as an American National Standard on December 27, 1972.

The 1981 revision included updating to the current ANSI standards format covering chains and sprockets. In the process of updating, the supplemental information (Appendices A and B) was reviewed and found to be inadequate with respect to selection information. The information was incomplete and could result in an unsatisfactory selection. Chain standards generally contained only dimensional and strength information to allow chains to be intercoupled. Therefore, the horsepower capacity information was deleted.

The American National Standards Institute approved that revision on April 3, 1981.

The 1991 revision added definitions for minimum ultimate strength (para. 2.2), measuring load (para. 2.3), and strand length tolerance (para. 2.4). M.U.T.S. values for chains 4020, 4824, and 5628 were increased. Other clarifications were made without changing the basic content.

The 1994 revision was approved by the American National Standards Institute on November 17, 1994.

This 1997 revision of ASME B29.10M was approved by the American National Standards Institute on July 22, 1997.

ASME COMMITTEE B29

Chains, Attachments, and Sprockets for Power Transmission and Conveying

(The following is the roster of the Committee at the time of approval of this Standard.)

OFFICERS

J. L. Wright, *Chair*
R. H. Uttke, *Vice Chair*
K. M. Padilla, *Secretary*

COMMITTEE PERSONNEL

E. B. Beardslee, Beardslee Transmission Equipment Co., Long Island City, New York
L. E. Hampel, Allied-Locke Industries, Inc., Dixon, Illinois
A. M. McCarty, Emerson Power Transmission, Ithaca, New York
D. Moore, Jeffrey Chain Co., Morristown, Tennessee
C. B. Norberg, Ithaca, New York
V. D. Petershake, Hitachi Maxco Ltd., Oconomowoc, Wisconsin
R. A. Reinfried, Conveyor Equipment Manufacturers Association, Manassas, Virginia
S. Rhoad, Webster Industries, Inc., Tiffin, Ohio
K. J. Smith, Drives, Inc., Fulton, Illinois
R. H. Uttke, Rexnord Corp., Milwaukee, Wisconsin
J. L. Wright, Diamond Chain Co., Indianapolis, Indiana
D. N. Zwiep, Worcester Polytechnic Institute, Worcester, Massachusetts
J. Kane, *Alternate*, U.S. Tsubaki Inc., Holyoke, Massachusetts
C. McDonald, *Alternate*, Jervis B. Webb Co., New Hudson, Michigan

CONTENTS

Foreword	iii
Standards Committee Roster	v
1 Nomenclature	1
2 General Chain Designators	1
3 Chain Assembly	2
4 Sprocket Tooth Form	2
Figures	
1 Heavy Duty Offset Sidebar Power Transmission Roller Chains	1
2 Chain Assembly	3
3 Sprocket Tooth Form	8
Tables	
1 General Chain Dimensions, M.U.T.S., Strand Length, and Measuring Load	4
2 Maximum and Minimum Controlling Link Dimensions for Interchangeable Chain Links	5
3 Chain Clearance Dimensions	7
4 Maximum Eccentricity and Face Runout Tolerances	9
5 Sprocket Tooth Form Factors	9

HEAVY DUTY OFFSET SIDEBAR POWER TRANSMISSION ROLLER CHAINS AND SPROCKET TEETH

1 NOMENCLATURE

A series of identical offset links in which the pins articulate inside the bushings and the rollers are free to turn on the bushings. Pins and bushings are fixed in their respective sidebar holes [Fig. 1, sketches (a) and (b)].

In addition to press fits, other types of locks such as flats are sometimes used to prevent rotation of pins and bushings in their respective sidebar holes.

2 GENERAL CHAIN DESIGNATORS

2.1 Dimensions for Chain Links

To assure interchangeability of links as produced by different makers of chain, standard maximum and minimum dimensions are adopted. They are not actual dimensions used in manufacturing, but limiting dimensions, maximum or minimum, required to assure the desired interchangeability.

All dimensions are given in a decimal-inch system. The metric equivalent dimensions are for reference only.

2.2 Numbering System

The standard chain numbers were based upon the inch system. The first two, or left hand digits in the chain designation denote the number of $\frac{1}{8}$ in. in the pitch. The last two, or right hand digits, denote the number of $\frac{1}{16}$ in. in the pin diameter.


2.3 Minimum Ultimate Tensile Strength (M.U.T.S.)

Minimum Ultimate Tensile Strength (M.U.T.S.), for chain covered by this Standard, is the minimum force at which an unused, undamaged chain could fail when subjected to a single tensile loading test.


WARNING:

(a) The *minimum ultimate tensile strength* is not a "working load." The M.U.T.S. greatly exceeds the maximum force that may be safely applied to the chain.

(b) Test Procedure: A tensile force is slowly applied, in uniaxial direction, to the ends of the chain sample.



(a)



(b)

FIG. 1 HEAVY DUTY OFFSET SIDEBAR POWER TRANSMISSION ROLLER CHAINS

(c) The tensile test is a destructive test. Even though the chain may not visibly fail when subjected to the "Minimum Ultimate Tensile Force," it will have been damaged and will be unfit for service.

CAUTION: This load is beyond the yield strength of the chain and would render the chain unsuitable for application. For application guidance, consult manufacturers' catalogs or the American Chain Association Handbook, "Engineering Steel Chains for Conveyors, Elevators and Drives."

2.4 Measuring Load

The measuring load, in pounds (or kilonewtons) in Table 1, is the load under which a dry or lightly lubricated chain should be measured for length.

2.5 Strand Length Tolerance

The length of new chains subject to the specified measuring load must fall within the plus and minus tolerances. *Specific maximum and minimum strand lengths are shown in Table 1, for each chain.*


3 CHAIN ASSEMBLY

See Fig. 2 and Tables 1, 2, and 3.

4 SPROCKET TOOTH FORM

See Fig. 3.

ASMENORMDOC.COM : Click to view the full PDF of ASME B29.10M 1997



- B = inside diameter of bushing
 D = pin diameter
 F = overall chain height
 H = roller diameter
 J = pin head to centerline
 K = pin end to centerline
 P = assembled chain pitch (this is a theoretical reference dimension used for basic calculations)
 T = sidebar thickness
 V = sidebar end clearance radius, open end of link
 V_a = sidebar end clearance radius, closed end of link
 W = inside width
 X = width of link at closed end extending through end clearance zone "Y"
 Y = sidebar end clearance zone, closed end of link
 Y_a = sidebar end clearance zone, open end of link
 Z = width between sidebars at open end of link extending through sidebar end clearance zone "Y_a"

FIG. 2 CHAIN ASSEMBLY

TABLE 1
GENERAL CHAIN DIMENSIONS, M.U.T.S., STRAND LENGTH,
AND MEASURING LOAD

Dimensions, in.								
Chain No.	2010	2512	2814	3315	3618	4020	4824	5628
<i>P</i>	2.500	3.067	3.500	4.073	4.500	5.000	6.000	7.000
<i>D</i>	0.625	0.750	0.875	0.938	1.100	1.250	1.500	1.750
<i>T</i>	0.31	0.38	0.50	0.56	0.56	0.62	0.75	0.88
<i>F</i>	1.75	2.25	2.25	2.38	3.00	3.50	4.00	5.00
<i>H</i>	1.25	1.62	1.75	1.78	2.25	2.50	3.00	3.50
<i>W</i>	1.50	1.56	1.50	1.94	2.06	2.75	3.00	3.25
M.U.T.S., lb (See para. 2.2) [Note (1)]	57,000	77,000	106,000	124,000	171,000	222,000	315,000	425,000
No. of Chain Pitches in Standard Measuring Length	48	39	34	30	27	24	20	17
Standard Measuring Length, in.								
Max.	120.38	119.99	119.38	122.57	121.88	120.38	120.38	119.38
Min.	120.00	119.61	119.00	122.19	121.50	120.00	120.00	119.00
Measuring Load, lb	400	600	800	900	1300	1700	2200	3300

Dimensions, mm								
<i>P</i>	63.50	77.90	88.00	103.45	114.30	127.00	152.40	177.80
<i>D</i>	15.88	19.05	22.22	23.83	27.94	31.75	38.10	44.45
<i>T</i>	7.9	9.7	12.7	14.2	14.2	15.7	19.1	22.4
<i>F</i>	44.5	57.2	57.2	60.5	76.2	88.9	101.6	127.0
<i>H</i>	31.8	41.1	44.5	45.2	57.2	63.5	76.2	88.9
<i>W</i>	38.1	39.6	38.1	49.3	52.3	69.9	76.2	82.6
M.U.T.S., kN (See para. 2.2) [Note (1)]	254	342	471	552	761	987	1401	1890
No. of Chain Pitches in Standard Measuring Length	48	39	34	30	27	24	20	17
Standard Measuring Length, mm								
Max.	3057.7	3047.7	3032.3	3113.3	3095.8	3057.7	3057.7	3032.3
Min.	3048.0	3038.1	3022.6	3103.6	3086.1	3048.0	3048.0	3022.6
Measuring Load, kN	1.8	2.7	3.6	4.0	5.8	7.6	9.8	14.7

CAUTION: The numerical values set forth in this Table do not afford a sufficient or appropriate basis for determining chain application and must be read in conjunction with the definitions and explanatory notes on page 1.

NOTE:

(1) M.U.T.S. is a factored statistical value for standards, which does not necessarily reflect the typical ultimate strength of the chain. Manufacturer should be consulted for additional information.

TABLE 2
MAXIMUM AND MINIMUM CONTROLLING LINK DIMENSIONS FOR
INTERCHANGEABLE CHAIN LINKS

		Dimensions, in.							
Chain No.		2010	2512	2814	3315	3618	4020	4824	5628
Chain Pitch	(P)	2.500	3.067	3.500	4.073	4.500	5.000	6.000	7.000
Pin Diameter, Max.	(D)	0.626	0.751	0.876	0.939	1.101	1.251	1.501	1.751
Inside Diameter of Bushing, Min.	(B)	0.628	0.753	0.879	0.942	1.105	1.255	1.506	1.757
Roller Diameter, Max.	(H)	1.250	1.625	1.750	1.781	2.250	2.500	3.000	3.500
Sidebar End Clearance Zone Closed End of Link, Min. [Note (1)]	(Y)	0.88	1.06	1.25	1.31	1.56	1.88	2.19	2.56
Sidebar End Clearance Zone Open End of Link, Min. [Note (1)]	(Y _a)	0.94	1.16	1.31	1.38	1.62	2.06	2.31	2.68
Sidebar End Clearance Radius Open End of Link, Max. [Note (1)]	(V)	0.88	1.06	1.25	1.31	1.56	1.88	2.19	2.56
Sidebar End Clearance Radius Closed End of Link, Max. [Note (1)]	(V _a)	0.94	1.16	1.31	1.38	1.62	2.06	2.31	2.68
Width of Link at Closed End, Extending Through End Clearance Zone "Y," Max.	(X)	2.141	2.328	2.520	3.082	3.207	4.031	4.531	5.031
Width Between Sidebars at Open End of Link Extending Through Sidebar End Clearance Zone "Y _a ," Min.	(Z)	2.146	2.333	2.525	3.087	3.212	4.036	4.536	5.036
Inside Width, Min.	(W)	1.44	1.50	1.44	1.86	1.98	2.64	2.88	3.12

(Table 2 continues on next page)

TABLE 2 (CONT'D)
MAXIMUM AND MINIMUM CONTROLLING LINK DIMENSIONS FOR
INTERCHANGEABLE CHAIN LINKS

		Dimensions, mm							
Chain No.		2010	2512	2814	3315	3618	4020	4824	5628
Chain Pitch	(P)	63.50	77.00	88.90	103.45	114.30	127.00	152.40	177.80
Pin Diameter, Max.	(D)	15.90	19.08	22.25	23.85	27.97	31.78	38.13	44.48
Inside Diameter of Bushing, Min.	(B)	15.95	19.13	22.33	23.93	28.07	31.88	38.25	44.63
Roller Diameter, Max.	(H)	31.75	41.28	44.45	45.24	57.15	63.50	76.20	88.90
Sidebar End Clearance Zone Closed End of Link, Min. [Note (1)]	(Y)	22.4	26.9	31.8	33.3	39.6	47.8	55.6	65.0
Sidebar End Clearance Zone Open End of Link, Min. [Note (1)]	(Y _a)	23.9	29.5	33.3	35.1	41.1	52.3	58.7	68.1
Sidebar End Clearance Radius Open End of Link, Max. [Note (1)]	(V)	22.4	26.9	31.8	33.3	39.6	47.8	55.6	65.0
Sidebar End Clearance Radius Closed End of Link, Max. [Note (1)]	(V _a)	23.9	29.5	33.3	35.1	41.1	52.3	58.7	68.1
Width of Link at Closed End, Extending Through End Clearance Zone "Y," Max.	(X)	54.38	59.13	64.01	78.28	81.46	102.39	115.09	127.79
Width Between Sidebars at Open End of Link Extending Through Sidebar End Clearance Zone "Y _a ," Min.	(Z)	54.51	59.26	64.14	78.41	81.58	102.51	115.21	127.91
Inside Width, Min.	(W)	36.6	38.1	36.6	47.2	50.3	67.1	73.2	79.2

GENERAL NOTE: Offset bend lines may be straight or curved. If curved, their radii Y and Y_a must be greater than V and V_a, respectively, so that the mating ends of links built to maximum dimensions will allow flexing around a 7-tooth sprocket.

NOTE:

- (1) Sidebar ends may be extended, provided the extension is within a 30 deg. included angle with respect to the end of sidebar as shown in Chain Assembly. Whether the sidebar ends are extended or not, the offset section of the bar must provide clearance for such an extension.

TABLE 3
CHAIN CLEARANCE DIMENSIONS

Dimensions, in.								
Chain No.	2010	2512	2814	3315	3618	4020	4824	5628
Pin Head to Center- (J) line, Max.	1.69	1.88	2.19	2.50	2.56	3.06	3.50	4.00
Pin End to Center- (K) line, Max.	1.88	2.19	2.44	2.81	3.00	3.56	3.88	4.50
Overall Chain (F) Height, Max.	1.88	2.38	2.38	2.50	3.12	3.62	4.12	5.25
Dimensions, mm								
Pin Head to Center- (J) line, Max.	42.9	47.8	55.6	63.5	65.0	77.7	88.9	101.6
Pin End to Center- (K) line, Max.	47.8	55.6	62.0	71.4	76.2	90.4	98.6	114.3
Overall Chain (F) Height, Max.	47.8	60.5	60.5	63.5	79.2	91.9	104.6	133.4