

REV.
C

AS1039

FEDERAL SUPPLY CLASS
4730





FIGURE 1 - TEE, BULKHEAD ON SIDE

TABLE 1 - DIMENSIONS AND WEIGHTS

BASIC NO. AS1039	/8/ /15/		LB/EA	LB/EA	LB/EA
	SIZE	CODE	MAX	MAX	MAX
	V	W	ALUM	CRES	TI
02	.312	.090	-	-	-
03	.375	.100	-	-	-
04	.438	.110	-	-	-
05	.500	.120	-	-	-
06	.562	.120	-	-	-
08	.750	.150	-	-	-
10	.875	.170	-	-	-
12	1.062	.185	-	-	-
16	1.312	.205	-	-	-
20	1.625	.240	-	-	-
24	1.875	.250	-	-	-
32	2.562	.350	-	-	-



CUSTODIAN: SAE G-3/G-3B PROCUREMENT SPECIFICATION: /3/ MIL-F-5509

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space
INTERNATIONAL
400 Commonwealth Drive, Warrendale, PA 15096-0001

AEROSPACE STANDARD
TEE, STANDARD AND REDUCER,
BULKHEAD ON SIDE, FLARED TUBE

AS1039
SHEET 1 OF 4

REV. C

ISSUED 1962-08 REVISED 1994-01 (C)

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

REV.
C

AS1039

TABLE 2 - LEG LENGTH B

SIZE OF PORT #3	FORGING SIZE /8/ 02	FORGING SIZE /8/ 03	FORGING SIZE /8/ 04	FORGING SIZE /8/ 05	FORGING SIZE /8/ 06	FORGING SIZE /8/ 08	FORGING SIZE /8/ 10	FORGING SIZE /8/ 12	FORGING SIZE /8/ 16	FORGING SIZE /8/ 20	FORGING SIZE /8/ 24	FORGING SIZE /8/ 32
02	1.429	1.461	1.507	1.538	1.648	1.789	1.929	2.039	2.164	2.445	2.726	3.133
03	-	1.461	1.507	1.538	1.648	1.789	1.929	2.039	2.164	2.445	2.726	3.133
04	-	-	1.601	1.632	1.742	1.883	2.023	2.133	2.250	2.539	2.820	3.227
05	-	-	-	1.632	1.742	1.883	2.023	2.133	2.250	2.539	2.820	3.227
06	-	-	-	-	1.820	1.961	2.101	2.211	2.336	2.617	2.898	3.305
08	-	-	-	-	-	2.117	2.257	2.367	2.492	2.773	3.054	3.461
10	-	-	-	-	-	-	2.398	2.508	2.633	2.914	3.195	3.602
12	-	-	-	-	-	-	-	2.679	2.804	3.085	3.366	3.773
16	-	-	-	-	-	-	-	-	2.804	3.085	3.366	3.773
20	-	-	-	-	-	-	-	-	-	3.132	3.413	3.820
24	-	-	-	-	-	-	-	-	-	-	3.429	3.836
32	-	-	-	-	-	-	-	-	-	-	-	4.117

TABLE 3 - LEG LENGTH D

SIZE OF PORT #1 OR #2	FORGING SIZE /8/ 02	FORGING SIZE /8/ 03	FORGING SIZE /8/ 04	FORGING SIZE /8/ 05	FORGING SIZE /8/ 06	FORGING SIZE /8/ 08	FORGING SIZE /8/ 10	FORGING SIZE /8/ 12	FORGING SIZE /8/ 16	FORGING SIZE /8/ 20	FORGING SIZE /8/ 24	FORGING SIZE /8/ 32
02	.851	.883	.883	.937	.993	1.158	1.260	1.373	1.482	1.669	1.716	2.031
03	-	.914	.905	.968	1.024	1.189	1.291	1.404	1.513	1.700	1.747	2.044
04	-	-	.976	1.039	1.095	1.260	1.362	1.475	1.584	1.771	1.818	2.115
05	-	-	-	1.039	1.095	1.260	1.362	1.475	1.584	1.771	1.818	2.115
06	-	-	-	-	1.101	1.266	1.368	1.481	1.590	1.777	1.824	2.121
08	-	-	-	-	-	1.367	1.469	1.582	1.691	1.878	1.925	2.222
10	-	-	-	-	-	-	1.570	1.683	1.792	1.979	2.026	2.323
12	-	-	-	-	-	-	-	1.789	1.898	2.085	2.132	2.429
16	-	-	-	-	-	-	-	-	1.945	2.132	2.179	2.476
20	-	-	-	-	-	-	-	-	-	2.179	2.226	2.523
24	-	-	-	-	-	-	-	-	-	-	2.351	2.648
32	-	-	-	-	-	-	-	-	-	-	-	2.898

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space
INTERNATIONAL

AEROSPACE STANDARDTEE, STANDARD AND REDUCER,
BULKHEAD ON SIDE, FLARED TUBE**AS1039**

SHEET 2 OF 4

REV.**C**

REV.
C

AS1039

TABLE 4 - TUBE SIZE AND CORRESPONDING THREAD

PORT SIZE	(NOMINAL	
	TUBE SIZE)	T THREAD PER MIL-S-8879
02	.125	.3125-24 UNJF
03	.188	.3750-24 UNJF
04	.250	.4375-20 UNJF
05	.312	.5000-20 UNJF
06	.375	.5625-18 UNJF
08	.500	.7500-16 UNJF
10	.625	.8750-14 UNJF
12	.750	1.0625-12 UNJ
16	1.000	1.3125-12 UNJ
20	1.250	1.6250-12 UNJ
24	1.500	1.8750-12 UNJ
32	2.000	2.5000-12 UNJ

NOTES:

/1/ MATERIAL:

- a. NO CODE LETTER - 1137 STEEL FORGING OR BAR PER AMS 5024 OR ASTM A 108, OR 4130 STEEL FORGING OR BAR PER AMS 6370 OR MIL-S-6758.
- b. CODE LETTER D - 2014T6 ALUMINUM ALLOY FORGING PER AMS 4133 OR QQ-A-367; OR 2024T6 ALUMINUM ALLOY BAR PER AMS 4112 OR QQ-A-225/6; OR 2024T851 ALUMINUM ALLOY BAR PER QQ-A-225/6.
- c. CODE LETTER J - 30304 CORROSION RESISTANT STEEL FORGING OR BAR PER AMS 5639 OR 304 CORROSION RESISTANT STEEL PER QQ-S-763.
- d. CODE LETTER K - 30316 CORROSION RESISTANT STEEL FORGING OR BAR PER AMS 5648 OR 316 CORROSION RESISTANT STEEL PER QQ-S-763.
- e. CODE LETTER S - 30347 CORROSION RESISTANT STEEL FORGING OR BAR PER AMS 5646 OR 347 CORROSION RESISTANT STEEL PER QQ-S-763.
- f. CODE LETTER T - 6AL4V TITANIUM ALLOY FORGING OR BAR PER AMS 4928.
- g. CODE LETTER W - 7075T73 ALUMINUM ALLOY FORGING PER AMS 4141 OR QQ-A-367; OR 7075T7351 ALUMINUM ALLOY BAR PER AMS 4124, OR 7075T73 ALUMINUM ALLOY BAR PER QQ-A-225/9.

2. FINISH:

- a. NO MATERIAL CODE LETTER - CADMIUM PLATE PER QQ-P-416, TYPE II, CLASS 2, DYE BLACK.
- b. MATERIAL CODE LETTER D - ANODIZE PER AMS 2472 OR MIL-A-8625, TYPE II, CLASS 2, DYE BLUE, DUPLEX SEAL.
- c. MATERIAL CODE LETTER J - PASSIVATE PER QQ-P-35, TYPE VI OR VII.
- d. MATERIAL CODE LETTER K - PASSIVATE PER QQ-O-35, TYPE VI OR VII.
- e. MATERIAL CODE LETTER S - PASSIVATE PER QQ-P-35, TYPE VI OR VII.
- f. MATERIAL CODE LETTER T - FLUORIDE PHOSPHATE CONVERSION COAT PER AMS 2486.
- g. MATERIAL CODE LETTER W - ANODIZE PER AMS 2472 OR MIL-A-8625, TYPE II, CLASS 2, DYE BROWN, DUPLEX SEAL.

- /3/ PROCUREMENT SPECIFICATION: MIL-F-5509 EXCEPT AS SPECIFIED ON THIS STANDARD. USERS OF THIS STANDARD ARE ADVISED TO CONTROL SOURCE APPROVAL(S) BY STANDARD PAGE SUPPLEMENT SHEET OR SIMILAR MEANS.