

Synchro, Torque Receiver Transmitter, Type 23TRX6B

FSC 5990

RATIONALE

This Revision consists of a 5 (five) year review, which provides updates to current format and references.

NOTICE

This specification is approved for use by all Departments and Agencies of the Department of Defense. The requirements for acquiring the Synchros described herein shall consist of this specification and the latest issue of SAE AS20708.

SAENORM.COM : Click to view the full PDF of as20708_56a

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2011 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
<http://www.sae.org>

SAE WEB ADDRESS:

**SAE values your input. To provide feedback
on this Technical Report, please visit
<http://www.sae.org/technical/standards/AS20708/56A>**

TABLE 1 – REQUIREMENTS

Requirement	Value	Unit	Tolerance
Frequency	60	Hz	±1%
Primary Voltage	115	volts	±1%
Primary Current	210.0	milliamps	maximum
Primary Power	5.6	watts	maximum
Impedance:			
Zss	110-145	ohms	min.-max.
Impedance Angle:			
Zss	10.0-17.0	degrees	min.-max.
Transformation Ratio	0.783	-----	±2%
Phase Shift (Lead)	11.0	degrees	maximum
Electrical Error	8.0	minutes	maximum
Receiver Error	45.0	minutes	maximum
Null Voltage:			
Total	160.0	millivolts	maximum
Fundamental	60.0	millivolts	maximum
Synchronizing Time			
30° ± 2°	1.0	seconds	maximum
Synchronizing Time:			
177° ± 2°	2.0	seconds	maximum
Torque Gradient	0.12	ounce-inches per degree	minimum
Radial Play	0.0010	inches	maximum
End Play	0.0025	inches	±0.0020
Temperature Rise	35.0	degrees (C)	maximum
Variation of Voltage			
(+10%) and Freq. (-5%)	8.1	watts	maximum

TABLE 2 – MILITARY PART NUMBER VARIANT CHARACTERISTICS

Military Part No. <u>1/</u>	A ± .010	B ± .010	G Maximum	Shaft Style	Terminal End	U + .0000 - .0002
M20708/56-01B	.676	.719	3.160	Splined	Terminal Board	.2405

1/ Military part number M20708/56-01B shall be the NATO standard.

1/ The suffix letter following the numerical dash number corresponds to the latest modification letter in the type designation.