

FEDERAL SUPPLY CLASS
4720

REV.
A

AS4573

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.





FIGURE 1 - HOSE ASSEMBLY, 90° ELBOW TO 90° ELBOW



(R) FIGURE 2 - ELBOWS ORIENTATION

ISSUED 1992-06
REVISED 1994-07 (A)

CUSTODIAN: SAE G-3/G-3D

PROCUREMENT SPECIFICATION: AS1975 /2/

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space
INTERNATIONAL
400 Commonwealth Drive, Warrendale, PA 15096-0001

AEROSPACE STANDARD

HOSE ASSEMBLY, PTFE, ARAMID REINFORCED,
STANDARD DUTY, 4000/3000 psi, 275 °F, TITANIUM
FITTINGS, FLARELESS, 90° TO 90°

AS4573

SHEET 1 OF 5

REV.

A

AS4573

REV. A

(R) TABLE 1 - ASSEMBLY DIMENSIONS

HOSE ASSEMBLY NO. & SIZE CODE	HOSE SIZE (REF)	THREAD T PER MIL-S-8879 (REF)	ID MIN (REF)	A MAX	B GAGE BASIC	D (REF)	E /B/		F HEX REF	G		BALL SIZE MIN THRU /7/ MS19059 DASH NO.	BALL SIZE MIN THRU /7/ DIA IN
							WITHOUT SLEEVING	MAX		MIN	MAX		
AS4573E	.250	.4375-20UNJF-3B	.212	1.880	.2930	.16	.69	.56	.790	.645	.790	4807	.109
AS4573G	.375	.5625-18UNJF-3B	.298	2.180	.4120	.16	.80	.69	.840	.715	.840	4812	.188
AS4573H	.500	.7500-16UNJF-3B	.391	2.530	.5600	.19	.97	.88	.970	.845	.970	4816	.313
AS4573J	.625	.8750-14UNJF-3B	.485	3.375	.6730	.20	1.15	1.00	1.210	1.085	1.210	4818	.375
AS4573K	.750	1.0625-12UNJ-3B	.602	3.940	.8100	.23	1.38	1.25	1.400	1.275	1.400	4821	.469
AS4573M	1.000	1.3125-12UNJ-3B	.852	4.485	1.0620	.30	1.66	1.50	1.625	1.500	1.625	4829	.719
AS4573N	1.250	1.5625-12UNJ-3B	1.100	5.225	1.3160	.04	2.33	1.81	1.825	1.700	1.825	4834	.875
AS4573P	1.500	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD

TABLE 2 - HOSE OR SLEEVE OUTSIDE DIAMETER

SLEEVE CODE	SLEEVE MATERIAL	TEMP LIMIT °F	TOLERANCE		HOSE SIZE /10/		HOSE SIZE /10/		HOSE SIZE /10/		HOSE SIZE /10/	
			MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN
-	BRAIDED HOSE ONLY PER AS1975	275	.465	.555	.715	.920	1.075	1.365	1.660	1.660	TBD	TBD
A	FIRESLEEVE (AS1072 SIL FG) (5 min) /11/ /12/	275	.840	.970	1.150	1.380	1.590	1.750	1.950	1.950	TBD	TBD
B	FIRESLEEVE INTEGRAL SILICONE (5 min) /8/	275	.658	.788	.968	1.198	1.318	1.568	1.768	1.768	TBD	TBD
C	PROTECTIVE SLEEVE SHRINK-ON (POLYOLEFIN AS1073, CODE B) /21/	275	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD

AS4573 REV. A

(R) TABLE 3 - ASSEMBLY LENGTH TOLERANCE

HOSE ASSEMBLY LENGTH	TOLERANCE
UNDER 18 in	±.125 in
18 THRU 36 in	±.250 in
OVER 36 THRU 50 in	±.500 in
OVER 50 in	±1%

(R) TABLE 4 - MAXIMUM HOSE AND FITTING WEIGHTS

HOSE OR SLEEVE CODE	HOSE OR TYPE OR PART	UNITS	HOSE SIZE						
-	BRAIDED HOSE ONLY PER AS1975	LB/IN	.006	.008	.012	.020	.025	.040	.050
A	FIRE SLEEVE AS1072 (5 min PER AS1055) /15/	LB/IN							
B	FIRE SLEEVE INTEGRAL WITH HOSE (5 min PER AS1055) /15/	LB/IN							
C	PROTECTIVE SLEEVE SHRINK-ON (POLYOLEFIN AS1073, CODE B) /21/	LB/IN							
NONE	FIRE SLEEVE CLAMP	LB/EA	.020	.020	.021	.021	.025	.025	.032
NONE	FITTING END (90°) TITANIUM /16/	LB/EA	.077	.121	.176	.310	.560	.950	TBD
									TBD /9/

SAENORM.COM: Click to view the full PDF of as4573a

 <p>SAE The Engineering Society For Advancing Mobility Land Sea Air and Space INTERNATIONAL</p>	<p>AEROSPACE STANDARD</p> <p>HOSE ASSEMBLY, PTFE, ARAMID REINFORCED, STANDARD DUTY, 4000/3000 psi, 275 °F, TITANIUM FITTINGS, FLARELESS, 90° TO 90°</p>	<p>AS4573</p> <p>SHEET 3 OF 5</p>	<p>REV.</p> <p>A</p>
--	--	--	------------------------------------

REV.
A

AS4573

NOTES:

1. MATERIALS:
 - a. HOSE AND FITTINGS PER AS1975
 - b. SLEEVES - SEE APPLICABLE STANDARDS, TABLE 2
- /2/ THIS HOSE ASSEMBLY SHALL BE QUALIFIED IN ACCORDANCE WITH PROCUREMENT SPECIFICATION AS1975. USERS OF THIS STANDARD ARE ADVISED TO CONTROL SOURCE APPROVAL(S) BY STANDARD PAGE SUPPLEMENT SHEET OR SIMILAR MEANS.
3. CONSTRUCTION AND PERFORMANCE PER AS1975. FITTINGS SHALL BE PERMANENTLY ATTACHED TO THE HOSE.
4. OPERATING CHARACTERISTICS PER AS1975.
5. MARKING: MARKING SHALL BE PER AS1975 ON A STAINLESS STEEL BAND NOT OVER 1.0 in WIDE OR ON THE COLLAR. THE CHARACTERS SHALL BE A MINIMUM OF .06 in HIGH. THE BAND SHALL BE SO DESIGNED AS TO REMAIN TIGHT ON THE HOSE TO PREVENT RELATIVE MOVEMENT AND RESULTANT CHAFING. IT SHALL BE OF SUFFICIENT STRENGTH TO PREVENT REMOVAL BY HAND. HOSE ASSEMBLY DATE AND "PT" SYMBOL SHALL BE ELECTROETCHED ON THE BAND OR ON AN END FITTING OR A FIRESLEEVE CLAMP. MARKING BAND SHALL BE COVERED WITH TRANSPARENT POLYOLEFIN SHRINK SLEEVE PER AS1073 CODE A.
- /6/ LENGTH "L" IS A THREE DIGIT NUMBER OF WHICH THE FIRST TWO DIGITS DESCRIBE THE HOSE ASSEMBLY LENGTH IN WHOLE INCHES, AND THE FOURTH DIGIT, THE FRACTION OF AN INCH IN EIGHTHS. LENGTH "L" IS MEASURED FROM "GAGE DIAMETER" TO "GAGE DIAMETER". FOR LENGTH INCREMENTS AND TOLERANCES SEE TABLE 3. "END TO END" LENGTH MEASUREMENTS IS THE SAME AS THE "GAGE DIAMETER" TO "GAGE DIAMETER" BECAUSE BOTH ENDS ARE 90° ELBOWS.
- /7/ A TRUE CIRCULAR CROSS SECTION IS NOT REQUIRED THROUGH THE FITTING ID. HOWEVER, THE APPLICABLE BALL DIAMETER LISTED IN TABLE 1 MUST BE CAPABLE OF PASSING THROUGH THE HOSE ASSEMBLY.
- /8/ DISTANCE ACROSS CORNERS OF THE HEX MAY EXCEED THIS DIMENSION.
- /9/ FITTING ENDS SIZE -4 THRU -16 MUST COMPLY TO NAS1760; FITTINGS FOR HOSE SIZE -20 AND LARGER TO COMPLY WITH AS4703. FITTINGS SHALL MATE WITH MS33514 FOR SIZES THRU -16 AND WITH AS4658 OR AS4659 IN SIZES -20 AND LARGER. -20 AND LARGER NUTS SHALL CONFORM TO AS4660 OR AS4702. STANDARD COUPLING NUTS SHALL BE IN ACCORDANCE WITH OR EQUIVALENT TO MS21921 OR MS27073. NUTS SHALL MEET TORQUE REQUIREMENTS PER AS1975.
- /10/ DIAMETERS ARE LISTED FOR CLAMP SELECTION. TUBULAR SLEEVES MAY NOT BE A PERFECT ROUND AND SHALL BE MEASURED WITH A DIAMETER TAPE RULE (OFTEN REFERRED TO AS A PI-TAPE).
- /11/ THE TABLE 2 SLEEVE DIAMETERS FOR AS1072 SLEEVES APPLY WHEN THE SLEEVE IS COMPRESSED, OR CLAMPED, TO CONTACT THE HOSE. IN THIS CASE, A WRINKLE MAY OCCUR OVER APPROXIMATELY 10% OF THE SLEEVE CIRCUMFERENCE.
- /12/ THE CUT ENDS OF THE FIRESLEEVE SHALL BE COATED WITH RTV SILICONE RUBBER PRIOR TO INSTALLATION TO PREVENT WICKING OF FLUIDS. THE FIRESLEEVE ENDS SHALL BE SECURED TO THE HOSE ASSEMBLY END FITTINGS WITH CORROSION RESISTANT STEEL BANDS. AFTER INSTALLATION, CRACKS OR VOIDS IN THE FIRESLEEVE, WHICH EXPOSE THE FIBERGLASS, SHALL BE COATED WITH RTV SILICONE RUBBER.
- /13/ THE END OF THE INTEGRAL FIRESLEEVE SHALL BE COVERED WITH SILICONE EXTENDING OVER THE END FITTING COLLAR.
14. ADD "AS1055 TYPE 1b CLASS A-S/P" TO IDENTIFICATION MARKING TO SHOW LEVEL OF COMPLIANCE, "FIRE (R) RESISTANT 275 °F (5 min), WITH AS1055".
- /15/ WHEN FIRESLEEVES ARE REQUIRED, WEIGHT LIMITS SHALL BE DEFINED BY THE PROCURING AUTHORITY.
- /16/ TITANIUM PARTS MAY BE REPLACED WITH STAINLESS STEEL IF MAXIMUM WEIGHT FOR FITTING IS NOT EXCEEDED.
17. DIMENSIONING AND TOLERANCING: ANSI Y14.5M
- /18/ THE FITTING'S ORIENTATION DASH NUMBER IS A THREE DIGIT NUMBER DEFINING THE RELATIVE POSITION OF THE END FITTINGS IN 1° INCREMENTS (EXAMPLE 090 = 90°). FITTING ORIENTATION SHALL BE MEASURED COUNTERCLOCKWISE FROM THE NEAREST END FITTING, WHICH SHALL BE IN THE RELATIVE 000° POSITION (SEE FIGURE 2). WHEN END FITTINGS ARE POINTED IN THE SAME DIRECTION, THIS DASH NUMBER SHALL BE 000.
19. LOCKWIRE HOLES LOCATION AND DIAMETER PER AS1043 CODED AS FOLLOWS:
 - a. U = TWO HOLES 180° APART
 - b. W = THREE HOLES 120° APART
20. THIS PART STANDARD TAKES PRECEDENCE IN CASES OF CONFLICT.

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space
INTERNATIONAL

AEROSPACE STANDARD

HOSE ASSEMBLY, PTFE, ARAMID REINFORCED,
STANDARD DUTY, 4000/3000 psi, 275 °F, TITANIUM
FITTINGS, FLARELESS, 90° TO 90°

AS4573

SHEET 4 OF 5

REV.**A**