

Connector Accessories, Electrical, Backshell, Environmental, Straight, Shield Termination, Category 2B
(For MIL-DTL-38999 I and II Connectors)

This amendment forms a part of AS85049/17A Dated 2007-06

1). Present Requirement: (Sheet 1)

The requirements for procuring the product described herein shall consist of this specification sheet and the latest issue of: SAE AS85049.

Change Requirements: (sheet 1)

NOTICE

The requirements for procuring the product described herein shall consist of this specification sheet and the latest issue of SAE AS85049.

Rationale for Change: Up-dated the procurement statement to comply with SAE guidelines.

2). Present Requirement: (Finish, sheet 3)

**FINISH: 1/ N - ELECTROLESS NICKEL
W - CADMIUM OLIVE DRAB**

**1/ N NOT FOR NAVY USE. LIMITED TO SPACE APPLICATION FOR AIR FORCE USE.
2/ W IS NOT FOR USE IN SPACE APPLICATIONS.**

Change Requirement: (Finish, sheet 3)

Finish:

- 1/ N Electroless Nickel
- 2/ W Cadmium, Olive Drab
- X Nickel Fluorocarbon Polymer
- 2/ Z Zinc Nickel

1/ N finish not for Navy use, restricted to Air Force space applications only.
2/ W and Z finish are not for use in space applications. Also see specification notes.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2010 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
http://www.sae.org

**SAE values your input. To provide feedback
on this Technical Report, please visit
http://www.sae.org/technical/standards/AS85049/17A_A1**

SAE WEB ADDRESS: