


SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV. B	FEDERAL SUPPLY CLASS 5306	
	RATIONALE THIS DOCUMENT HAS BEEN DETERMINED TO CONTAIN BASIC AND STABLE TECHNOLOGY WHICH IS NOT DYNAMIC IN NATURE. STABILIZED NOTICE THIS DOCUMENT HAS BEEN DECLARED "STABILIZED" BY THE SAE E-25 GENERAL STANDARDS FOR AEROSPACE AND PROPULSION SYSTEMS COMMITTEE AND WILL NO LONGER BE SUBJECTED TO PERIODIC REVIEWS FOR CURRENCY. USERS ARE RESPONSIBLE FOR VERIFYING REFERENCES AND CONTINUED SUITABILITY OF TECHNICAL REQUIREMENTS. NEWER TECHNOLOGY MAY EXIST.	
AS91711	SAENORM.COM : Click to view the full PDF of as91711b	
CUSTODIAN: E-25		THIRD ANGLE PROJECTION 
	AEROSPACE STANDARD BOLT, MACHINE - DOUBLE HEXAGON EXTENDED WASHER HEAD, DRILLED, PD SHANK, BLACK OXIDE, STEEL, UNS G87400, 125 KSI MIN .3125-24 UNF-3A	AS91711
		REV. B

THE INITIAL SAE PUBLICATION OF THIS DOCUMENT WAS TAKEN DIRECTLY FROM U.S. MILITARY STANDARD MS9171A. THIS SAE STANDARD RETAINS THE SAME PART NUMBERS ESTABLISHED BY THE ORIGINAL MILITARY DOCUMENT.

ANY REQUIREMENTS ASSOCIATED WITH QUALIFIED PRODUCTS LISTS (QPL) MAY CONTINUE TO BE MANDATORY FOR DOD CONTRACTS. REQUIREMENTS RELATING TO QPL'S HAVE NOT BEEN ADOPTED BY THE SAE FOR THIS STANDARD AND ARE NOT PART OF THIS SAE DOCUMENT.

SAENORM.COM : Click to view the full PDF of as91711b

	AEROSPACE STANDARD	AS91711 SHEET 1 OF 4	REV. B
	BOLT, MACHINE - DOUBLE HEXAGON EXTENDED WASHER HEAD, DRILLED, PD SHANK, BLACK OXIDE, STEEL, UNS G87400, 125 KSI MIN .3125-24 UNF-3A		

TABLE 1 - PART NUMBERS AND DIMENSIONS.

PART NUMBER	L	K	APPROX. MASS LB/100	PART NUMBER	L	K	APPROX. MASS LB/100
MS9171-05	.552 - .572	1/	2.21	MS9171-32	2.740 - 2.760	1.815 - 1.875	6.13
MS9171-06	.615 - .635	1/	2.28	MS9171-33	2.865 - 2.885	1.940 - 2.000	6.36
MS9171-07	.678 - .698	1/	2.39	MS9171-34	2.990 - 3.010	2.065 - 2.125	6.58
MS9171-08	.740 - .760	1/	2.51	MS9171-35	3.115 - 3.135	2.190 - 2.250	6.80
MS9171-09	.802 - .822	1/	2.62	MS9171-36	3.240 - 3.260	2.315 - 2.375	7.03
MS9171-10	.865 - .885	1/	2.73	MS9171-37	3.365 - 3.385	2.440 - 2.500	7.27
MS9171-11	.928 - .948	1/	2.85	MS9171-38	3.490 - 3.510	2.565 - 2.625	7.50
MS9171-12	.990 - 1.010	.065 - .125	2.96	MS9171-39	3.615 - 3.635	2.690 - 2.750	7.73
MS9171-13	1.052 - 1.072	.128 - .188	3.07	MS9171-40	3.740 - 3.760	2.815 - 2.875	7.95
MS9171-14	1.115 - 1.135	.190 - .250	3.19	MS9171-41	3.865 - 3.885	2.940 - 3.000	8.17
MS9171-15	1.178 - 1.198	.252 - .312	3.30	MS9171-42	3.990 - 4.010	3.065 - 3.125	8.40
MS9171-16	1.240 - 1.260	.315 - .375	3.41	MS9171-43	4.115 - 4.135	3.190 - 3.250	8.63
MS9171-17	1.302 - 1.322	.378 - .438	3.52	MS9171-44	4.240 - 4.260	3.315 - 3.375	8.86
MS9171-18	1.365 - 1.385	.440 - .500	3.64	MS9171-45	4.365 - 4.385	3.440 - 3.500	9.08
MS9171-19	1.428 - 1.448	.502 - .562	3.75	MS9171-46	4.490 - 4.510	3.565 - 3.625	9.30
MS9171-20	1.490 - 1.510	.565 - .625	3.87	MS9171-47	4.615 - 4.635	3.690 - 3.750	9.52
MS9171-21	1.552 - 1.572	.628 - .688	3.98	MS9171-48	4.740 - 4.760	3.815 - 3.875	9.74
MS9171-22	1.615 - 1.635	.690 - .750	4.10	MS9171-49	4.865 - 4.885	3.940 - 4.000	9.95
MS9171-23	1.678 - 1.698	.752 - .812	4.22	MS9171-50	4.990 - 5.010	4.065 - 4.125	10.17
MS9171-24	1.740 - 1.760	.815 - .875	4.33	MS9171-51	5.115 - 5.135	4.190 - 4.250	10.40
MS9171-25	1.865 - 1.885	.940 - 1.000	4.55	MS9171-52	5.240 - 5.260	4.315 - 4.375	10.63
MS9171-26	1.990 - 2.010	1.065 - 1.125	4.77	MS9171-53	5.365 - 5.385	4.440 - 4.500	10.86
MS9171-27	2.115 - 2.135	1.190 - 1.250	5.00	MS9171-54	5.490 - 5.510	4.565 - 4.625	11.10
MS9171-28	2.240 - 2.260	1.315 - 1.375	5.23	MS9171-55	5.615 - 5.635	4.690 - 4.750	11.33
MS9171-29	2.365 - 2.385	1.440 - 1.500	5.45	MS9171-56	5.740 - 5.760	4.815 - 4.875	11.56
MS9171-30	2.490 - 2.510	1.565 - 1.625	5.67	MS9171-57	5.865 - 5.885	4.940 - 5.000	11.78
MS9171-31	2.615 - 2.635	1.690 - 1.750	5.90	MS9171-58	5.990 - 6.010	5.065 - 5.125	12.00

1/ THREAD TO HEAD. MAXIMUM TWO IMPERFECT THREADS.

**AEROSPACE STANDARD**

BOLT, MACHINE - DOUBLE HEXAGON EXTENDED
 WASHER HEAD, DRILLED, PD SHANK, BLACK
 OXIDE, STEEL, UNS G87400, 125 KSI MIN
 .3125-24 UNF-3A

AS91711
 SHEET 3 OF 4

REV.
B