



# SURFACE VEHICLE RECOMMENDED PRACTICE

J1512

MAY2014

Issued 1985-06  
Stabilized 2014-05

Superseding J1512 JUL2008

## Manual Slack Adjuster Performance Requirements

### RATIONALE

This technical report, SAE J1512, is being Stabilized because it covers technology, products, or processes which are mature and not likely to change in the foreseeable future.

### STABILIZED NOTICE

This document has been declared "Stabilized" by the SAE Truck and Bus Foundation Brake Committee and will no longer be subjected to periodic reviews for currency. Users are responsible for verifying references and continued suitability of technical requirements. Newer technology may exist.

SAENORM.COM : Click to view the full PDF of J1512-201405

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2014 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

**TO PLACE A DOCUMENT ORDER:** Tel: 877-606-7323 (inside USA and Canada)  
Tel: +1 724-776-4970 (outside USA)  
Fax: 724-776-0790  
Email: CustomerService@sae.org  
<http://www.sae.org>

SAE WEB ADDRESS:

**SAE values your input. To provide feedback  
on this Technical Report, please visit  
[http://www.sae.org/technical/standards/J1512\\_201405](http://www.sae.org/technical/standards/J1512_201405)**