

	SURFACE VEHICLE RECOMMENDED PRACTICE	
	SAE	J2350 NOV2012
	Issued Stabilized	1997-03 2012-11
Superseding J2350 MAR2002		
Electric Blower Motor Switch - Trucks, Buses, and Multipurpose Vehicles		

RATIONALE

This standard should be "Stabilized" because it covers technology which is mature and not likely to change in the foreseeable future and there is not expertise on the committee available to recommend any revisions.

STABILIZED NOTICE

This document has been declared "Stabilized" by the SAE Truck and Bus Windshield Wipers and Climate Control Committee and will no longer be subjected to periodic reviews for currency. Users are responsible for verifying references and continued suitability of technical requirements. Newer technology may exist.

SAENORM.COM : Click to view the full PDF of J2350_201211

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2012 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
 Tel: +1 724-776-4970 (outside USA)
 Fax: 724-776-0790
 Email: CustomerService@sae.org
 SAE WEB ADDRESS: <http://www.sae.org>

**SAE values your input. To provide feedback
 on this Technical Report, please visit
http://www.sae.org/technical/standards/J2350_201211**

1. Scope—This SAE Recommended Practice establishes for trucks, buses, and multipurpose passenger vehicles with GVW of 4500 kg (10 000 lb) or greater:

- a. Minimum performance requirements for the electric blower motor switch.
- b. Uniform test procedures that include those tests that can be conducted on uniform test equipment by commercially available laboratory facilities.

2. References

2.1 Related Publications—The following publications are provided for information purposes only and are not a required part of this document.

2.1.1 SAE PUBLICATION—Available from SAE, 400 Commonwealth Drive, Warrendale, PA 15096-0001.

SAE J235—Electric Blower Motor Switch

2.1.2 ISO PUBLICATION—Available from ANSI, 25 West 43rd Street, New York, NY 10036-8002.

ISO 3468—Passenger Car—Windscreen Defrosting System

3. Definitions

3.1 Electric Blower Motor Switch—That part of a defrosting/defogging system by which the operator of a vehicle causes a blower motor to function.

4. Temperature Test

4.1 To insure basic function, the switch shall be manually cycled for 10 cycles at design electrical load at $24\text{ }^{\circ}\text{C} \pm 5.5\text{ }^{\circ}\text{C}$ ($75\text{ }^{\circ}\text{F} \pm 10\text{ }^{\circ}\text{F}$); $74, +0, -2.8\text{ }^{\circ}\text{C}$ ($165, +0, -5\text{ }^{\circ}\text{F}$); and $-32, +2.8, -0\text{ }^{\circ}\text{C}$ ($-25, +5, -0\text{ }^{\circ}\text{F}$) after a 1 h exposure at each of these temperatures. The switch shall be electrically and mechanically operable during each of these cycles.

4.2 This same switch shall be used for the endurance test described in Section 5.