



SURFACE VEHICLE RECOMMENDED PRACTICE	J2629™	AUG2015
	Issued	2011-06
	Stabilized	2015-08
Superseding J2629 JUN2011		
Standard Formats for Presenting Acoustical Data		

RATIONALE

The committee cannot find users for the technical report.

STABILIZED NOTICE

This document has been declared "Stabilized" by the SAE Acoustical Materials Committee and will no longer be subjected to periodic reviews for currency. Users are responsible for verifying references and continued suitability of technical requirements. Newer technology may exist.

SAENORM.COM : Click to view the full PDF of j2629_201508

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2015 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
http://www.sae.org

SAE WEB ADDRESS:

SAE values your input. To provide feedback on this Technical Report, please visit
http://www.sae.org/technical/standards/J2629_201508

INTRODUCTION

Acoustical test results for standardized SAE and ASTM test procedures as well as non-standardized vehicle test procedures can be presented in a number of formats and scalings, making comparison(s) of results difficult in many cases. This document addresses the need for a consistent format for the presentation of various acoustical material, part and vehicle interior noise test data.

TABLE OF CONTENTS

1.	SCOPE.....	2
1.1	Purpose.....	2
2.	REFERENCES.....	2
2.1	Applicable Documents.....	2
2.1.1	SAE Publications.....	3
2.1.2	ASTM Publications.....	3
3.	DEFINITIONS.....	3
3.1	Modified Articulation Index.....	3
4.	PROCEDURES.....	4
5.	TEST DATA.....	4
6.	TEST SAMPLES.....	4
7.	TEST FACILITIES.....	4
8.	TEST FORMATS.....	4
8.1	Vehicle Level Testing of Materials, Components and Systems on the Road or Chassis Dynamometer.....	4
8.2	Material and Component Testing in the Laboratory.....	5
9.	NOTES.....	5
9.1	Marginal Indicia.....	5
9.2	General Comments.....	5

SAENORM.COM : Click to view the full PDF of J2629_201508

APPENDIX A	INFORMATION FOR THE SAE J2629 SPREADSHEETS.....	6
FIGURE 1	VEHICLE ROAD DATA - A-WEIGHTED SOUND PRESSURE LEVEL VERSUS ENGINE SPEED	8
FIGURE 2	VEHICLE DYNO DATA - A-WEIGHTED SOUND PRESSURE LEVEL VERSUS ENGINE SPEED	9
FIGURE 3	VEHICLE ROAD DATA - A-WEIGHTED SOUND PRESSURE LEVEL VERSUS 1/3 OCTAVE FREQUENCY.....	10
FIGURE 4	VEHICLE DYNO DATA - A-WEIGHTED SOUND PRESSURE LEVEL VERSUS 1/3 OCTAVE FREQUENCY.....	11
FIGURE 5	VEHICLE ROAD DATA - MODIFIED ARTICULATION INDEX VERSUS ENGINE SPEED	12
FIGURE 6	VEHICLE DYNO DATA - MODIFIED ARTICULATION INDEX VERSUS ENGINE SPEED	13
FIGURE 7	SAE J1400 SOUND TRANSMISSION LOSS.....	14
FIGURE 8	ASTM C 423 RANDOM INCIDENCE SOUND ABSORPTION.....	15
FIGURE 9A	ASTM E 1050 NORMAL INCIDENCE SOUND ABSORPTION - 1/3 OCTAVE FREQUENCIES	16
FIGURE 9B	ASTM E 1050 NORMAL INCIDENCE SOUND ABSORPTION - NARROW BAND FREQUENCIES.....	17
FIGURE 10	SAE J1637 COMPOSITE DAMPING LOSS FACTOR	18
FIGURE 11A	SAE J1637 COMPOSITE DAMPING LOSS FACTOR - 10 TO 1000 Hz	19
FIGURE 11B	SAE J1637 COMPOSITE DAMPING LOSS FACTOR - 100 TO 10 000 Hz	20

1. SCOPE

SAE developed this document and associated spreadsheets at the request of automobile manufacturers to help compare products from multiple suppliers using standard data presentation formats. This document includes several preferred formats for presenting acoustical data on materials, components, systems or vehicles. These formats cover the range of acoustical tests commonly conducted in the automotive industry. These tests follow SAE and ASTM test practices as well as vehicle specific test methods.

For each test, the details of samples and test conditions can be entered into an applicable electronic spreadsheet together with the acoustical results data. These data are then linked to standard graphical display(s) for each test. All manufacturers and suppliers in this industry are encouraged to present data and results in these formats.

Although this practice was developed specifically for use in the automotive industry, the formats may be usable in other industries and applications as well.

1.1 Purpose

This document establishes recommended practices and formats for reporting of common acoustical results.

2. REFERENCES

2.1 Applicable Documents

The following publications form a part of this specification to the extent specified herein. Unless otherwise indicated, the latest issue of SAE publications shall apply.

2.1.1 SAE Publications

Available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or 724-776-4970 (outside USA), www.sae.org.

SAE J1400 Laboratory Measurement for the Airborne Sound Barrier Performance of Automotive Materials and Assemblies

SAE J1637 Laboratory Measurement of the Composite Vibration Damping Properties of Materials on a Supporting Steel Bar

2.1.2 ASTM Publications

Available from ASTM International, 100 Barr Harbor Drive, P.O. Box C700, West Conshohocken, PA 19428-2959, Tel: 610-832-9585, www.astm.org.

ASTM C 423 Standard Test Method for Sound Absorption and Sound Absorption Coefficients by the Reverberation Room Method

ASTM E 1050 Standard Test Method for Impedance and Absorption of Acoustical Materials Using a Tube, Two Microphones, and a Digital Frequency Analysis System

ASTM C 384 Standard Test Method for Impedance and Absorption of Acoustical Materials by the Impedance Tube Method

ASTM E 756 Standard Test Method for Measuring Vibration-Damping Properties of Materials

3. DEFINITIONS

3.1 Modified Articulation Index

Modified Articulation Index (MAI) is calculated according to the following weighting factors and reference levels for respective 1/3 octave sound pressure measurements.

$$\text{MAI}_{200} = 3.33/100*(64 - \text{dBL}_{200})$$

$$\text{MAI}_{250} = 6.67/100*(69 - \text{dBL}_{250})$$

$$\text{MAI}_{315} = 10.83/100*(71 - \text{dBL}_{315})$$

$$\text{MAI}_{400} = 14.17/100*(73 - \text{dBL}_{400})$$

$$\text{MAI}_{500} = 15.00/100*(75 - \text{dBL}_{500})$$

$$\text{MAI}_{630} = 17.50/100*(75 - \text{dBL}_{630})$$

$$\text{MAI}_{800} = 21.67/100*(74 - \text{dBL}_{800})$$

$$\text{MAI}_{1000} = 24.17/100*(72 - \text{dBL}_{1000})$$

$$\text{MAI}_{1250} = 28.33/100*(70 - \text{dBL}_{1250})$$

$$\text{MAI}_{1600} = 38.33/100*(67 - \text{dBL}_{1600})$$

$$\text{MAI}_{2000} = 36.67/100*(65 - \text{dBL}_{2000})$$

$$\text{MAI}_{2500} = 31.67/100*(63 - \text{dBL}_{2500})$$

$$\text{MAI}_{3150} = 30.00/100*(60 - \text{dBL}_{3150})$$

$$\text{MAI}_{4000} = 25.83/100*(56 - \text{dBL}_{4000})$$

$$\text{MAI}_{5000} = 20.83/100*(51 - \text{dBL}_{5000})$$

$$\text{MAI}_{6300} = 8.33/100*(51 - \text{dBL}_{6300})$$

Where, for example at 200 Hz, 3.33 is the weighting factor, 64 is the reference level and dBL₂₀₀ is the linear or unweighted noise level for the 200 Hz 1/3 octave band frequency at the measurement location.

Corresponding data for all 1/3 octave bands from 250 to 6300 Hz are used in the MAI calculation.

MAI = sum of MAI₂₀₀ through MAI₆₃₀₀; usually expressed as a percent (100% or higher = perfect intelligibility).

NOTE: This metric uses weighting factors common to the automotive industry; but, which are slightly different than similar standards such as ANSI S3.5.

3.2 For all other definitions, see the respective test standards.

4. PROCEDURES

All data collected either from standard test methods or company specific test methods can be presented in corresponding display formats. These formats include descriptions of the samples and test conditions, followed by a graphical display of the results.

Each display format corresponds to an applicable spreadsheet that can be used to enter test data as well as descriptions of the sample and the test facility. This information is then automatically transferred to a spreadsheet tab containing a graphical display of the results with pre-set axis sizes, scales, and legends. Instructions for its use are shown on the first tab of each applicable SAE J2629 spreadsheet, which are directly downloadable within a single compressed file from SAE following the purchase of this standard.

5. TEST DATA

The template for each graphical display accepts data in the rectangular Cartesian coordinate system where the horizontal axis is the x- axis or abscissa and the vertical axis is the y- axis or ordinate. The range of independent variables (x-values) covers the conditions of greatest interest to the automobile manufacturers. The range of dependent variables (y-values) covers a wide dynamic range. In situations when dependent variables fall outside of the fixed dynamic range, data will appear on the graphical display at the top or bottom of the scale. However, the range selected for each display will generally prevent this from occurring.

Significant figures for data should be based on the accuracy inherent in the measurement system and as specified in the test method.

6. TEST SAMPLES

Depending on the type of test conducted, the test sample may be a flat material, a molded component, a sub-system or an entire vehicle. The template provides a data field to enter a description of the test sample. These details should describe the key physical characteristics and establish a baseline for comparisons to other samples included in the same graphical display. The user may add additional information beyond the items listed in the template.

7. TEST FACILITIES

The template requires details covering the test facility and test conditions, providing a reference to the source of the test data and to the engineer and/or technician who conducted the test. In some cases, these details may help explain differences in data between identical samples tested at different test facilities.

8. TEST FORMATS

Graphical displays have been prepared to cover the following test formats. For each test type, the graphical display has a fixed length and scale for each axis.

8.1 Vehicle Level Testing of Materials, Components and Systems on the Road or Chassis Dynamometer

- Vehicle Road Test Data - A-weighted Sound Pressure Level versus Engine Speed, shown per Figure 1.
- Vehicle Dyno Test Data - A-weighted Sound Pressure Level versus Engine Speed, shown per Figure 2.
- Vehicle Road Test Data - A-weighted Sound Pressure versus 1/3 Octave Frequency, shown per Figure 3.
- Vehicle Dyno Test Data - A-weighted Sound Pressure versus 1/3 Octave Frequency, shown per Figure 4.
- Vehicle Road Test Data - Modified Articulation Index versus Engine Speed, shown per Figure 5.
- Vehicle Dyno Test Data - Modified Articulation Index versus Engine Speed, shown per Figure 6.

8.2 Material and Component Testing in the Laboratory

- Sound Transmission Loss per SAE J1400, shown per Figure 7.
- Random Incidence Sound Absorption per ASTM C 423, shown per Figure 8. Note that sound absorption values for frequencies beyond those valid for ASTM C 423 are shown for reference only.
- Normal Incidence Sound Absorption per ASTM E 1050 (1/3 octave or narrow band), shown per Figures 9A and 9B.
- Composite Vibration Damping per SAE J1637 (temperature), shown per Figure 10.
- Composite Vibration Damping per SAE J1637 (frequency), shown per Figures 11A and 11B.

9. NOTES

9.1 Marginal Indicia

A change bar (I) located in the left margin is for the convenience of the user in locating areas where technical revisions, not editorial changes, have been made to the previous issue of this document. An (R) symbol to the left of the document title indicates a complete revision of the document, including technical revisions. Change bars and (R) are not used in original publications, nor in documents that contain editorial changes only.

9.2 General Comments

These SAE data formats are recommended for presentations to automobile manufacturers and for use by acoustic integrators, interior integrators, tier I suppliers, and other material suppliers. This SAE practice provides the best means for a user to then compare data on competitive materials, components, systems, or vehicles.

These data formats are to be used for data collected according to the commonly used test formats and test procedures listed in Section 5. The data collected from these tests, however, should not be considered as the only data that can be presented to an automobile manufacturer or other user. Additional data from other tests may also be presented using a format selected by the supplier or the user. In all cases, this additional information should be a supplement to the formats described in this document and not a replacement.

To avoid duplication of effort in presenting data, test facilities are encouraged to supply data to their test requestors using these formats. These formats can then be readily used in presentations to automobile manufacturers or to other users. This will also minimize errors generated when data is converted from one format to the SAE recommended format.

In the future, revisions to these formats will be made to meet the ongoing needs of the users, which include both vehicle manufacturers and suppliers. Additional data formats may be added as new test practices are developed.

Following purchase of the SAE J2629 text document and associated spreadsheets, instructions will be provided for downloading a single compressed file containing a collection of spreadsheets from the SAE web site¹. Use standard computer operating system utilities for uncompressing the collection of spreadsheets to your computer storage device.

For questions or problems on the use of the SAE J2629 electronic spreadsheets, SAE may be contacted at CustomerService@sae.org.

¹This downloadable file contains a set of applicable SAE standard spreadsheets (the "Spreadsheets"). The Spreadsheets are copyrighted works and all rights, title and interest in and to the Spreadsheets are owned by SAE International. SAE hereby grants you a nonexclusive, nontransferable license to use the Spreadsheets and to prepare one derivative work based on each Spreadsheet (the "Derivative") provided that the SAE copyright notice appears on each Derivative as "© 2011 SAE International," you agree that the use of any information contained in each Spreadsheet is provided "AS IS" and is entirely at your risk as the licensee, and you hereby indemnify SAE from any and all claims or damages caused by your use, modification, sale or application of the Spreadsheets and any Derivatives. Under no circumstances shall SAE International be liable for any costs, losses, expenses or damages (whether direct or indirect, consequential, special, economic, or financial, including any losses of profits) whatsoever that may be incurred through the use of any information contained in the spreadsheets. © 2011 SAE International.

APPENDIX A - INFORMATION FOR THE SAE J2629 SPREADSHEETS

MINIMUM SYSTEM REQUIREMENTS

The following minimum system and software requirements are required to use the SAE J2629 spreadsheets:

PC capable of running Microsoft Excel 97 or newer;
256 megabytes of memory or greater;
Microsoft Excel 97 or newer


Instructions to use the SAE J2629 Spreadsheets:

1. Uncompress the single compressed file downloaded from SAE at the time of purchase (see 9.2)
2. Extract the collection of spreadsheets to an appropriate location on a PC storage device
3. Select and open the appropriate spreadsheet from the following
 - a. Random Incidence Sound Absorption per ASTM C 423
 - b. Normal Incidence Sound Absorption per ASTM E 1050 (1/3 octave or narrow band)
 - c. Sound Transmission Loss per SAE J1400
 - d. Composite Vibration Damping per SAE J1637 (10 to 1000 Hz)
 - e. Composite Vibration Damping per SAE J1637 (100 to 10 000 Hz)
 - f. Composite Vibration Damping per SAE J1637 (temperature)
 - g. Vehicle Dyno Test Data - dBA versus 1/3 Octave Band Frequency
 - h. Vehicle Dyno Test Data - dBA versus Engine Speed
 - i. Vehicle Dyno Test Data - MAI versus Engine Speed
 - j. Vehicle Road Test Data - dBA versus 1/3 Octave Band Frequency
 - k. Vehicle Road Test Data - dBA versus Engine Speed
 - l. Vehicle Road Test Data - MAI versus Engine Speed
4. Click on the tab titled "Input Descriptions" and enter descriptions of the test sample and test conditions in the following fields (in white data entry fields).
 - a. Subtitle
 - b. Description of each sample, with physical properties
 - c. Test conditions and information
 - d. Other details in appropriate text fields
5. Click on the tab titled "Input Data" and enter test data as x and y coordinates in the appropriate columns (highlighted in gray).

6. Click on the tab titled "User Notes & Comments" to enter any other information.
7. When all data have been entered, click on the tab titled "Results pg1" to view the graphical display of results.
8. Click on the tab titled "Results pg2" to view the test information and data.
9. Revisions to the result graphs may be made by returning to the tabs "Input Descriptions" or "Input Data".
10. Any of these displays can be printed or copied into a presentation.
11. When all data entry is completed, save the file to a hard drive or a storage device with a unique file name.

The graphical display can be printed as a separate sheet or can be inserted in a PowerPoint presentation using the commands Copy and Paste Special from the Microsoft Excel application. See Figures 1 through 11.

SAENORM.COM : Click to view the full PDF of j2629_201508




Project Number:

Test Conditions:
 Test lab:
 Road location:
 Road surface:
 Speed:
 Vehicle gear:
 Vehicle load:
 Microphone or binaural head:
 Mic or head location:
 Number of averages:
 Test number:
 Test date:
 Test temperature - deg. C:
 Wind speed and direction:
 Test engineer/technician:

Notes and Comments

SAENORM.COM : Click to view the full PDF of J2629 - 201508

FIGURE 1 - VEHICLE ROAD DATA - A-WEIGHTED SOUND PRESSURE LEVEL VERSUS ENGINE SPEED




Project Number:

Test Conditions:
 Test lab:
 Rolls Turning (Frt, Rr, All):
 Roll surface:
 Speed:
 Vehicle gear:
 Vehicle load:
 Microphone or binaural head:
 Mic or head location:
 Number of averages:
 Test number:
 Test date:
 Test engineer/technician:

Notes and Comments


SAENORM.COM : Click to view the full PDF of J2629 - 201508

FIGURE 2 - VEHICLE DYNO DATA - A-WEIGHTED SOUND PRESSURE LEVEL VERSUS ENGINE SPEED




Project Number	Freq	Test A	Test B	Test C	Test D
Test Conditions	31.5	72.0	68.0	67.0	69.0
Test lab:	40	73.0	69.0	68.0	70.0
Road location:	50	73.0	70.0	69.0	71.0
Road surface:	63	74.0	71.0	70.0	72.0
Vehicle speed:	80	74.0	71.0	70.0	72.0
Vehicle gear:	100	75.0	73.0	72.0	74.0
Vehicle load:	125	74.0	70.0	69.0	71.0
Vehicle load:	160	72.0	69.0	68.0	70.0
Microphone or binaural	200	74.0	67.0	66.0	68.0
Mic or head location:	250	71.0	65.0	64.0	66.0
Number of averages:	315	69.0	63.0	62.0	64.0
Test number:	400	68.0	62.0	61.0	63.0
Test date:	500	66.0	61.0	60.0	62.0
Test temperature - deg. C:	630	68.0	60.0	59.0	61.0
Wind speed and direction:	800	65.0	59.0	58.0	60.0
Test engineer/technician:	1000	62.0	58.0	57.0	59.0
	1250	58.0	56.0	55.0	57.0
	1600	57.0	54.0	53.0	55.0
Notes and Comments	2000	57.0	52.0	51.0	53.0
	2500	58.0	50.0	49.0	51.0
	3150	56.0	48.0	47.0	49.0
	4000	53.0	47.0	46.0	48.0
	5000	50.0	45.0	44.0	46.0
	6300	46.0	43.0	42.0	44.0
	8000	43.0	42.0	41.0	43.0
	10000	40.0	40.0	39.0	41.0

FIGURE 3 - VEHICLE ROAD DATA - A-WEIGHTED SOUND PRESSURE LEVEL VERSUS 1/3 OCTAVE FREQUENCY



Project Number	Freq	Test A	Test B	Test C	Test D
Test Conditions	31.5	72.0	68.0	67.0	69.0
Test lab:	40	73.0	69.0	68.0	70.0
Road location:	50	73.0	70.0	69.0	71.0
Road surface:	63	74.0	71.0	70.0	72.0
Vehicle speed:	80	74.0	71.0	70.0	72.0
Vehicle gear:	100	75.0	73.0	72.0	74.0
Vehicle load:	125	74.0	70.0	69.0	71.0
Microphone or binaural	160	72.0	69.0	68.0	70.0
Mic or head location:	200	74.0	67.0	66.0	68.0
Number of averages:	250	71.0	65.0	64.0	66.0
Test number:	315	69.0	63.0	62.0	64.0
Test date:	400	68.0	62.0	61.0	63.0
Test engineer/technician:	500	66.0	61.0	60.0	62.0
	630	68.0	60.0	59.0	61.0
	800	65.0	59.0	58.0	60.0
	1000	62.0	58.0	57.0	59.0
	1250	58.0	56.0	55.0	57.0
	1600	57.0	54.0	53.0	55.0
Notes and Comments	2000	57.0	52.0	51.0	53.0
	2500	58.0	50.0	49.0	51.0
	3150	56.0	48.0	47.0	49.0
	4000	53.0	47.0	46.0	48.0
	5000	50.0	45.0	44.0	46.0
	6300	46.0	43.0	42.0	44.0
	8000	43.0	42.0	41.0	43.0
	10000	40.0	40.0	39.0	41.0

FIGURE 4 - VEHICLE DYNO DATA - A-WEIGHTED SOUND PRESSURE LEVEL VERSUS 1/3 OCTAVE FREQUENCY




Project Number

Test Conditions
 Test lab:
 Road location:
 Road surface:
 Vehicle speed:
 Vehicle gear:
 Vehicle load:
 Microphone or binaural head:
 Mic or head location:
 Number of averages:
 Test number:
 Test date:
 Test temperature - deg. C:
 Wind speed and direction:
 Test engineer/technician:

Notes and Comments

SAENORM.COM : Click to view the full PDF of J2629 - 201508

FIGURE 5 - VEHICLE ROAD DATA - MODIFIED ARTICULATION INDEX VERSUS ENGINE SPEED




Project Number

Test Conditions
 Test lab:
 Rolls Turning (Frt, Rr, All):
 Roller surface:
 Vehicle speed:
 Vehicle gear:
 Vehicle load:
 Microphone or binaural head:
 Mic or head location:
 Number of averages:
 Test number:
 Test date:
 Test engineer/technician:

Notes and Comments


FIGURE 6 - VEHICLE DYNO DATA - MODIFIED ARTICULATION INDEX VERSUS ENGINE SPEED



Project number	Freq.	Sample A	Sample B	Sample C	Sample D
	125	8.0	8.4	5.4	11.4
Test Description	160	11.8	12.8	9.8	15.8
Date tested:	200	14.8	16.6	13.6	19.6
Test location:	250	18.1	19.2	16.2	22.2
Ambient temp. [°C]:	315	17.1	18.4	15.4	21.4
Relative humidity [%]:	400	19.9	17.6	14.6	20.6
Atmospheric Pressure [kPa]:	500	25.3	17.9	14.9	20.9
	630	30.0	24.2	21.2	27.2
	800	35.6	31.9	28.9	34.9
Added Information	1000	40.6	37.3	34.3	40.3
Other sample description:	1250	45.9	43.0	40.0	46.0
SAE J1400 revision date:	1600	51.7	48.6	45.6	51.6
Test engineer/technician:	2000	59.5	54.5	51.5	57.5
	2500	66.6	59.9	56.9	62.9
	3150	72.5	67.1	64.1	70.1
	4000	77.2	74.5	71.5	77.5
	5000	81.3	79.2	76.2	82.2
	6300	85.0	83.3	80.3	86.3
	8000	88.5	87.7	84.7	90.7
	10000	92.1	92.0	89.0	95.0

Notes and Comments

FIGURE 7 - SAE J1400 SOUND TRANSMISSION LOSS



Project number	Freq	Sample A	Sample B	Sample C	Sample D
Test Description	125	0.14	0.10	0.20	0.08
Date tested:	160	0.15	0.11	0.21	0.09
Test location:	200	0.17	0.12	0.22	0.10
Chamber volume:	250	0.18	0.13	0.23	0.11
Test area size:	315	0.21	0.14	0.24	0.12
Segments per sample:	400	0.24	0.19	0.29	0.17
Ambient temp. [°C]:	500	0.42	0.26	0.36	0.24
Relative humidity [%]:	630	0.47	0.33	0.43	0.31
Atmospheric Pressure [kPa]:	800	0.72	0.40	0.50	0.38
Sealing of edges:	1000	0.96	0.47	0.57	0.45
Tape	1250	0.99	0.54	0.64	0.52
Angle iron	1600	1.04	0.61	0.71	0.59
Other	2000	1.08	0.68	0.78	0.66
Added Information	2500	1.09	0.75	0.85	0.73
Other sample description:	3150	1.07	0.82	0.92	0.80
Mounting condition:	4000	1.06	0.89	0.99	0.87
Air gap:	5000	1.04	0.96	1.06	0.94
Test engineer/technician:	6300	1.11	1.03	1.13	1.01
ASTM C-423 revision date:	8000	1.05	1.10	1.20	1.08
	10000	0.97	1.17	1.20	1.15

Notes and Comments

FIGURE 8 - ASTM C 423 RANDOM INCIDENCE SOUND ABSORPTION